

DB-2 Polyethylene Swing Door




-
- It complies with sanitary measures.
Manufactured in PVC
 - Value for money
 - Easy installation

DB-2 Polyethylene Swing Door

Superior quality polyethylene hinged door for intensive use, framed with anodized aluminum profile. Robust, durable and with an excellent aesthetic finish and sanitary suitability.


The DB-2 model is manufactured as standard in 15mm thick white PVC. As an option, the color of the polyethylene finish can be chosen (on request). It is a high-performance door, designed to have a minimum maintenance.



Sanitary suitability



Availability of various measures



Easy to assemble and maintain

Description

- Swing door made of food grade PVC with two leaves. Indicated for separating work rooms or air-conditioned warehouses with intense traffic.
- Aesthetics integrated into the rest of an installation made with sandwich panels.
- Door with excellent finish, high performance, with minimal maintenance and sanitary suitability.

DIPPANEL Doors stand out for:

- Quality of finishes
- Easy assembly and installation
- Adaptability to customer needs

Technical characteristics

FRAMEWORK

PROFILE

- Pre-frame type "U"
- White lacquered veneer 1006
- Manufactured to each thickness of existing panel on site
- Fixed with hidden screws and adaptable to different thicknesses

LEAF

PROFILE

- Anodized extruded aluminum (stainless)
- High corrosion resistance treatment

COMPOSITION

- White PVC

THICKNESS

- 15mm

VIEWFINDER

- 6mm thick methacrylate circular viewer
- 225mm diameter

BURLETTE

- Very flexible, double-celled and resistant to negative temperatures

IRONWORK

OPENINGS

- Double action hinges made of polyamide and stainless steel shaft
- 90° opening hold

SCREWS

- A2 stainless steel

OPTIONS

- Leaf finish in polyethylene in various colors (consult and always on request).
- Lower protection up to 400mm with checkerboard sheet, 5mm white polyethylene or stainless steel leaf.
- Aircraft wing type protection made of 5mm thick aluminum, 3mm stainless steel or black polyethylene (consult options and always on request).

DB-2 door details





dippanel

CONTACTO:

- (+34) 954 436 422
- (+34) 675 534 289
- info@dippanel.com

Avd. Dólmenes de Valencina, 6
41907. Valencina de la Concepción.
Seville. Spain